



HARMONY  
RAILING®



PREMIUM ALUMINUM  
RAILING, FENCING AND  
DECKING SYSTEMS

PRODUCT  
CATALOG

## ABOUT US

Harmony Railing® products offers a variety of luxury outdoor living products that beautifully complete any outdoor oasis. Our systems are safe, low maintenance and elevate the look of decks, patios, and pool areas across the country.

## STRONG AND SAFE

Our dedication to research and development ensures a safe, uniquely engineered railing system that meets commercial and residential codes throughout the country.

## LOW MAINTENANCE

Harmony's high-performance products are made of durable aluminum and coated with an AkzoNobel custom-blended Interpon D Series AAMA 2604 textured powder coating.

Harmony Railing® products are backed by a 20-year limited warranty against manufacturing defects, cracking, chipping, blistering or peeling under normal use and weather conditions.


## BEAUTY AND STYLE

We offer a variety of classic and modern railing styles. Our railing is manufactured with premium powder-coated aluminum that creates a beautiful look and is soft to touch. All systems are available in multiple colors.




**Baluster Panel System in Black**


## HARMONY RAILING, FENCING AND DECKING SYSTEMS




Standard Baluster




Continuous Baluster




42" Open Mid-Rail Baluster  
Special Order Only. Not available in all areas.




Vertical Cable




Horizontal Cable - Full Frame




Horizontal Cable - Top Rail Only




Drink Rail




Glass



ADA Handrail



Screen Rail



Fence



Aluminum Framing



**PREMIUM DESIGN**  
Hidden fasteners, no welds or rivets, elegant top rails



**FULL PRODUCT LINE**  
Gate kits, lights, ADA handrails and parts



**STRENGTH AND DURABILITY**  
Textured Powder-Coated Aluminum. Engineered, tested and approved as per ICC-ES AC273 and is IBC/IRC code compliant.



**PREASSEMBLED PANELS**  
Fast and easy installation



**CONVENIENT KITS**  
Simple planning and ordering

## COLORS AND STYLES

### TEXTURED COLOR OPTIONS



**BLACK**



**WHITE**



**BRONZE**



**PIANO RAIL®**

White with Black infill.



**TUXEDO RAIL®**

Black with White infill.

Colors vary by monitors and printing process. See actual samples for accurate color.

### TOP RAIL PROFILES



**VICTORIAN**



**ALTA**




**DRINK RAIL**

Drink Rail Attachment Kit Required

## ALUMINUM RAILING SPECIFICATIONS

- 36in H x 6ft W Deck and Stair Panels Actual Size: 34in H X 69.43in W
- 36in H x 8ft W Deck and Stair Panels Actual Size: 34in H X 91.31in W
- 42in H x 6ft W Deck Panels Actual Size: 39in H X 69.43in W
- 42in H x 8ft W Deck Panels Actual Size: 39in H X 91.31in W
- 42in H x 6ft W Stair Panels Actual Size: 41.43in H X 69.43in W
- Standard Balustrade Dimensions = 0.5in x 0.75in (.050in wall), Spacing = 3.875in
- Victorian Top Rail: 2.25in H x 2.25in W (.055in wall)
- Alta Top Rail: 1.833in H x 2.25in W (.055in wall)
- Bottom Rail - 1.5in x 1.5in (.050in wall)
- 3in x 3in Post - Actual Lengths: 38.25in, 43.5in and 48in (.065in wall)
- 2in x 2in Posts - Actual Lengths: 34.06in, 39.625in and 48in (.09in wall)
- Standard Baluster Gate Kits - Actual Sizes: 33.9in H X 38in W or 39.5in H X 38in W for up to 39in and 49in openings
- Wide Baluster Gate Kits - Actual Sizes: 33.9in H X 48in W or 39.5in H X 48in W for up to 39in and 49in openings
- Horizontal and Cable Gate Kits - Actual Sizes: 33.9in H X 49in W or 39.5in H X 49in W for up to 50in openings

# BALUSTER PANEL SYSTEM



**PREASSEMBLED ALUMINUM PANELS**

## RAILING PANELS


### Victorian

36in H x 6ft W P/N HR362306  
 42in H x 6ft W P/N HR362406  
 36in H x 8ft W P/N HR362308  
 42in H x 8ft W P/N HR362408

### Alta

36in H x 6ft W P/N HR862306  
 42in H x 6ft W P/N HR862406  
 36in H x 8ft W P/N HR862308  
 42in H x 8ft W P/N HR862408

B=Black, W=White, Z=Bronze.  
 Piano and Tuxedo available special order only.



## STAIR RAILING PANELS

### Victorian


36in H x 6ft W P/N HS352306  
 42in H x 6ft W P/N HS352406  
 36in H x 8ft W P/N HS352308  
 42in H x 8ft W P/N HS352408

### Alta

36in H x 6ft W P/N HS852306  
 42in H x 6ft W P/N HS852406  
 36in H x 8ft W P/N HS852308  
 42in H x 8ft W P/N HS852408

B=Black, W=White, Z=Bronze.  
 Piano and Tuxedo available special order only.

# CONTINUOUS RAILING SYSTEM




## RAILING PANELS

36in H x 6ft W P/N HR062306  
 42in H x 6ft W P/N HR062406  
 36in H x 8ft W P/N HR062308  
 42in H x 8ft W P/N HR062408

B=Black, W=White, Z=Bronze

**NOTE:** Top rails sold separately with continuous railing system




## STAIR RAILING PANELS

36in H x 6ft W P/N HS052306  
 42in H x 6ft W P/N HS052406  
 36in H x 8ft W P/N HS052308  
 42in H x 8ft W P/N HS052408


B=Black, W=White, Z=Bronze

**NOTE:** Top rails sold separately with continuous railing system



**Note:** 2in Posts are used with the Continuous Railing System.

# DRINK RAIL SYSTEM



## RAILING PANELS

(SAME AS CONTINUOUS RAIL SYSTEM)

36in H x 6ft W P/N HR062306  
 42in H x 6ft W P/N HR062406  
 36in H x 8ft W P/N HR062308  
 42in H x 8ft W P/N HR062408

B=Black, W=White, Z=Bronze



## DRINK RAIL KITS

Includes 4 color matched clips, 8 #8 3/4in Self-tapping SS screws, 16 #8 3/4in type 17 phillips stainless steel mod truss K-Lath screws.

Black = P/N BR094203BK  
 White = P/N BR094203WK  
 Bronze = P/N BR094203ZK


### Bottom Rail Snaps

6ft Snap P/N SH093106  
 8ft Snap P/N SH093108

B=Black, W=White, Z=Bronze


**Choose your own top rail - typically a deck board to match the deck surface.**

**Each 8ft Section Requires:** one Railing Panel, six Drink Rail Clips (2/3 of a kit) and one Bottom Rail Snap. For 6ft sections, only four Drink Rail Clips are required.



**NOTE:** For the Drink Rail System, the Bottom Rail Snap (SH093106 or SH093108) is used as the Top Rail Snap which supports the bracket and the Drink Rail. The panels to order are the continuous top rail panels (they do not include a top rail snap).

# VERTICAL CABLE RAILING SYSTEM



## 36IN VERTICAL CABLE PANELS

- 36in H x 6ft W Victorian Deck P/N VC662306
- 36in H x 8ft W Victorian Deck P/N VC662308
- 36in H x 6ft W Alta Deck P/N VC162306
- 36in H x 8ft W Alta Deck P/N VC162308
- 36in H x 6ft W Victorian Stair P/N VC652306
- 36in H x 6ft W Alta Stair P/N VC152306

## 42IN VERTICAL CABLE PANELS

- 42in H x 6ft W Victorian Deck P/N VC662406
- 42in H x 8ft W Victorian Deck P/N VC662408
- 42in H x 6ft W Alta Deck P/N VC162406
- 42in H x 8ft W Alta Deck P/N VC162408
- 42in H x 6ft W Victorian Stair P/N VC652406
- 42in H x 6ft W Alta Stair P/N VC152406



## 36IN CONTINUOUS VERTICAL CABLE PANELS\*

- 36in H x 6ft W Continuous Deck P/N VC088306
- 36in H x 8ft W Continuous Deck P/N VC088308
- 36in H x 6ft W Continuous Stair P/N VC058306

## 42IN CONTINUOUS VERTICAL CABLE PANELS\*

- 42in H x 6ft W Continuous Deck P/N VC088406
- 42in H x 8ft W Continuous Deck P/N VC088408
- 42in H x 6ft W Continuous Stair P/N VC058406

B=Black, W=White, Z=Bronze




Actual panel heights: 33.5in and 39in. Actual panel lengths: 69.43in and 91.31in. 3in posts are required to reach 6ft and 8ft lengths on center. System uses standard 3in aluminum posts. Top Rail Snaps are included.

Continuous Top Rail Systems are used with 2in posts and do not include top rail snaps. Top rail snaps are sold separately in 18ft lengths.

\*These kits can also be used as Sub-Assembly Replacement Kits.


# 1/4IN TEMPERED GLASS RAILING SYSTEM



## 6FT FULL PANEL GLASS RAIL SECTION

Actual panel length = 69.43in. Glass and Top Rails are not included and must be purchased separately. P/N HGO31206

B=Black, W=White, Z=Bronze



1/4in Tempered Glass Panels not included.

# HORIZONTAL CABLE RAILING SYSTEMS



Full Frame Kits (with bottom rail)



Top Rail Only Kits (without bottom rail)



## 36IN / 42IN FULL FRAME KITS

36/42in H x 6ft W Victorian Deck P/N TF661306  
 36/42in H x 8ft W Victorian Deck P/N TF661308  
 36/42in H x 6ft W Alta Deck P/N TF161306  
 36/42in H x 8ft W Alta Deck P/N TF161308

36/42in H x 6ft W Victorian Stair P/N TF651306  
 36/42in H x 8ft W Victorian Stair P/N TF651308  
 36/42in H x 6ft W Alta Stair P/N TF151306  
 36/42in H x 8ft W Alta Stair P/N TF151308

B=Black, W=White, Z=Bronze



## 36IN / 42IN CONTINUOUS FULL FRAME KITS\*

36/42in H x 6ft W Continuous Deck P/N TF068306  
 36/42in H x 8ft W Continuous Deck P/N TF068308  
 36/42in H x 6ft W Continuous Stair P/N TF058306  
 36/42in H x 8ft W Continuous Stair P/N TF058308

B=Black, W=White, Z=Bronze



## 36IN / 42IN TOP RAIL KITS

36/42in H x 6ft W Victorian Deck P/N TR661306  
 36/42in H x 8ft W Victorian Deck P/N TR661308  
 36/42in H x 6ft W Alta Deck P/N TR161306  
 36/42in H x 8ft W Alta Deck P/N TR161308

36/42in H x 6ft W Victorian Stair P/N TR651306  
 36/42in H x 8ft W Victorian Stair P/N TR651308  
 36/42in H x 6ft W Alta Stair P/N TR151306  
 36/42in H x 8ft W Alta Stair P/N TR151308

B=Black, W=White, Z=Bronze



## 36IN / 42IN CONTINUOUS TOP RAIL KITS\*

36/42in H x 6ft W Continuous Deck P/N TR068306  
 36/42in H x 8ft W Continuous Deck P/N TR068308  
 36/42in H x 6ft W Continuous Stair P/N TR058306  
 36/42in H x 8ft W Continuous Stair P/N TR058308

B=Black, W=White, Z=Bronze

## SPECIFICATIONS:

- Actual panel heights: 33.5in H and 39in H. Actual Panel Lengths: 69.43in W and 91.31in W.
- 3in posts are required to reach 6ft and 8ft lengths on center.
- System requires Horizontal Cable Aluminum Posts.
- Full Frame Kits include a bottom rail; Top Rail Kits do not.
- The horizontal cable kits are used for both 36in and 42in systems.
- 36in Full Frame Systems require 9 horizontal cables; Top Rail Systems require 10 horizontal cables.
- 42in Full Frame Systems require 11 horizontal cables; Top Rail Systems require 12 horizontal cables.
- 36in and 42in Continuous Top Rail Systems are used with 2in posts and do not include top rail snaps. Top rail snaps are sold separately in 18ft lengths.
- Cable kits are designed for level or stair surfaces.

\*These kits can also be used as Sub-Assembly Replacement Kits.

# HORIZONTAL CABLE RAILING SYSTEMS



## HORIZONTAL CABLE 3IN ALUMINUM POST KITS

These pre-drilled posts are required for the horizontal cable systems. Kits include: assembled post and base plate, post cap and post base plate vinyl skirt. Stair end posts include beveled washers. All posts below are for 36in and 42in horizontal cable systems. 42in posts are used for 42in systems, and are used for the bottom stair post on a 36in system.



### 36IN SYSTEMS

- 36in H x 3in W End Deck Post P/N PC6E1336
- 36in H x 3in W Inline Deck Post P/N PC6I1336
- 36in H x 3in W Corner Deck Post P/N PC6C1336
- 42in H x 3in W Inline Stair Post P/N PC6S1342
- 42in H x 3in W Stair Bottom Post P/N PC6B1342

### 36IN CONTINUOUS SYSTEMS

- 36in H x 2in W End Deck Post P/N PC6E1236
- 36in H x 2in W Inline Deck Post P/N PC6I1236
- 36in H x 2in W Corner Deck Post P/N PC6C1236
- 42in H x 2in W Inline Stair Post P/N PC6S1242



### 42IN SYSTEMS

- 42in H x 3in W End Deck Post P/N PC6E1342
- 42in H x 3in W Inline Deck Post P/N PC6I1342
- 42in H x 3in W Corner Deck Post P/N PC6C1342
- 48in H x 3in W Inline Stair Post P/N PC6S1348
- 48in H x 3in W Stair Bottom Post P/N PC6B1348

### 42IN CONTINUOUS SYSTEMS

- 42in H x 2in W End Deck Post P/N PC6E1242
- 42in H x 2in W Inline Deck Post P/N PC6I1242
- 42in H x 2in W Corner Deck Post P/N PC6C1242
- 48in H x 2in W Inline Stair Post P/N PC6S1248
- 48in H x 2in W Stair Bottom Post P/N PC6B1248

B=Black, W=White, Z=Bronze

Post-to-deck mount screws/anchors sold separately. 3in x 3in Posts actual lengths are 38.25in, 43.5in and 48in.



## HORIZONTAL CABLE KITS

These kits are designed for the horizontal cable systems. Each kit includes: (1) 1/8in stainless steel cable with pre-attached threaded stud in 5ft to 60ft lengths (increments of 5ft), (1) 1/8in threaded receiver fitting, (1) 1/8in fast receiver fitting and (2) stainless end caps. Full Frame Kits require 9 cables. Top Rail Kits require 10 cables. If exceeding 60ft in length, another cable kit and two end posts are required to start another run.

### HORIZONTAL CABLE KITS FOR 3IN POSTS

- |                      |                      |                      |                      |
|----------------------|----------------------|----------------------|----------------------|
| 5ft Kit P/N CW60305  | 20ft Kit P/N CW60320 | 35ft Kit P/N CW60335 | 50ft Kit P/N CW60350 |
| 10ft Kit P/N CW60310 | 25ft Kit P/N CW60325 | 40ft Kit P/N CW60340 | 55ft Kit P/N CW60355 |
| 15ft Kit P/N CW60315 | 30ft Kit P/N CW60330 | 45ft Kit P/N CW60345 | 60ft Kit P/N CW60360 |

### HORIZONTAL CABLE KITS FOR 2IN POSTS

- |                      |                      |                      |                      |
|----------------------|----------------------|----------------------|----------------------|
| 5ft Kit P/N CW90205  | 20ft Kit P/N CW90220 | 35ft Kit P/N CW90235 | 50ft Kit P/N CW90250 |
| 10ft Kit P/N CW90210 | 25ft Kit P/N CW90225 | 40ft Kit P/N CW90240 | 55ft Kit P/N CW90255 |
| 15ft Kit P/N CW90215 | 30ft Kit P/N CW90230 | 45ft Kit P/N CW90245 | 60ft Kit P/N CW90260 |

## CABLE TOOLS



Cable Gripper Tool TC097606  
Designed for use with Irwin VISE- GRIP® Straight Jaw Locking Pliers Model #302L3-7R (not included).



Horizontal Cable Tool Kit TK32750  
Includes: cable threading tool, 90° cable threading tool and cable release tool.



Stainless Steel Cable Cutter TC697703

# ALUMINUM POST KITS



## 3IN ALUMINUM POST KITS

Includes: assembled post and base plate, post cap and post base plate vinyl skirt.

36in H x 3in W P/N HK441336  
 42in H x 3in W P/N HK441342  
 48in H x 3in W P/N HK441348

B=Black, W=White, Z=Bronze

Post-to-deck mount screws/  
 anchors sold separately.

3in x 3in Posts - Actual Lengths =  
 38.25in, 43.5in and 48in.



## 2IN ALUMINUM POST KITS

Includes: assembled post and base plate, post base plate vinyl skirt, straight cross-over bracket and two #8 x 1.5in self-tapping screws.

36in H x 2in W P/N HK341236  
 42in H x 2in W P/N HK341242  
 48in H x 2in W P/N HK341248

B=Black, W=White, Z=Bronze

Post-to-deck mount screws/  
 anchors sold separately.

2in x 2in Posts - Actual Lengths =  
 34.06in, 39.625in and 48in.

# GATE KITS



Kits include gate, self-closing hinges and keyed latching hardware.

## BALUSTER GATE KITS

For openings up to 49in wide. Actual heights: 33.9in and 39.5in, actual width: 48in.

48in W x 36in H Baluster Gate Kit P/N HG07518  
 48in W x 42in H Baluster Gate Kit P/N HG07520

## VERTICAL CABLE GATE KITS

Adjustable width for openings up to 50in wide. Actual heights: 33.9in and 39.5in, actual width: 49in.

49in W x 36in H Vertical Cable Gate Kit P/N CG601349  
 49in W x 42in H Vertical Cable Gate Kit P/N CG601449

## HORIZONTAL CABLE GATE KITS

49in W x 36in H Horizontal Cable Gate Kit  
 Adjustable width for openings up to 50in wide.  
 Actual height: 33.9in, actual width: 49in. P/N CG681349

49in W x 42in H Horizontal Cable Gate Kit  
 For 50in wide openings. **Width is not adjustable.**  
 Actual height: 39.5in, actual width: 49in. P/N CG681449

B=Black, W=White, Z=Bronze






# HARDWARE



## RAIL CLIP JIG/TOUCH-UP PAINT

Ensures proper placement of the lower rail clips when attaching to posts. Touch-up paint is included for use when cutting extrusions. P/N HJ39700  
B=Black, W=White, Z=Bronze




## CONTINUOUS TOP RAIL SNAP

For use with continuous rail panels and 2in posts. 18ft Length. Victorian P/N VT393118  
Alta P/N AL893118  
B=Black, W=White, Z=Bronze



## DECK & STAIR PANEL ATTACH KIT

Required when deck or stair panel is cut and attaching more than one section. P/N HC39500



## 22.5° PANEL ATTACH KIT

Required for 45° deck corners. Refer to installation instructions for proper post placement. P/N HC06422




## 45° WALL MOUNT KIT

Required for 45° wall applications. Not to be used for post applications. P/N HC06445



## STRAIGHT WALL MOUNT KIT FOR BALUSTER AND GLASS PANELS

Used to secure deck panels to structural surface without a post for support. Victorian P/N HC39100  
Alta P/N HC89100  
B=Black, W=White, Z=Bronze



## ALTA CORNER KITS

90° Corner P/N HC801290  
45° Corner P/N HC801245  
B=Black, W=White, Z=Bronze



## 22.5° GLASS PANEL ATTACH KIT

Required for 45° deck corners. Refer to installation instructions for proper post placement. P/N HC03422  
B=Black, W=White, Z=Bronze



## GLASS PANEL ATTACH KIT

Required when deck panel is cut and attaching more than one section. P/N HC03400  
B=Black, W=White, Z=Bronze



## BOTTOM SNAP COLLAR KITS

For applications without a top snap. Cover mis-cuts to top or bottom rails. Deck P/N BH061202  
Stair P/N BH051202  
B=Black, W=White, Z=Bronze



## CUT COLLAR KITS

For applications with a top snap. Cover mis-cuts to a top rail snap and bottom rail. Victorian Deck P/N VT361202  
Victorian Stair P/N VT351202  
Alta Deck P/N AL061202  
Alta Stair P/N AL051202  
B=Black, W=White, Z=Bronze



## TOP RAIL END CAPS

For use with the continuous rail system. Victorian P/N VE19400  
Alta P/N AL825101  
B=Black, W=White, Z=Bronze

# LIGHTING AND ACCESSORIES



### 3IN LED POST CAP PERIMETER LIGHT

.3 watts, 3 LEDS, 39 Lumens, 4,000 Kelvin  
P/N: LE045310  
B=Black, W=White, Z=Bronze



### 3IN LED POST CAP INDIRECT LIGHT

1.2 watts, 12 LEDS (3 LEDS per side),  
156 Lumens, with an approximate effective  
Lumen output of 39 Lumens, 4,000 Kelvin  
P/N: LE045311  
B=Black, W=White, Z=Bronze



### SOLAR 3IN LED POST CAP PERIMETER LIGHT

3 Lumens, 3,000 Kelvin  
P/N: LSO45310  
B=Black, W=White, Z=Bronze



### 3IN LOW PROFILE POST CAP

(without light)  
P/N CC025303  
B=Black, W=White, Z=Bronze



### POWER PACK

12V 100W single tap,  
built in adjustable timer  
and photo cell.  
P/N: LE095101



### UR WIRE CONNECTORS

10 Pack. Replacement part;  
also included with post cap  
lights.  
P/N LE095104



### 100FT 16/2 GA WIRE

P/N LE095103

# REPLACEMENT PARTS

RAILING PANEL PARTS	
Victorian Top Rail Snap - 6ft	VT393106
Victorian Top Rail Snap - 8ft	VT393108
Alta Top Rail Snap - 6ft	AL893106
Alta Top Rail Snap - 8ft	AL893108
Bottom Rail Snap - 6ft	SH093106
Bottom Rail Snap - 8ft	SH093108
Victorian Continuous Top Rail Snap - 18ft Length	VT393118
Alta Continuous Top Rail Snap - 18ft Length	AL893118
SMALL PARTS	
Support Leg w/ color screw	SL09403K
3IN POST PARTS	
Base Plate Vinyl Skirt for 3in Post	BC015305
Post Cap for 3in Post (Standard)	CC044300
Low Profile 3in Post Cap	CC025303
2IN POST PARTS	
Base Plate Vinyl Skirt for 2in Post	BC015204
2in Crossover Bracket	CL044204
2in Stair Crossover Bracket	CL04425
HARDWARE	
#8x3/4in Self-tapping Screws 16/pack	ST09934K
#8 x 1-1/2in Self-tapping Screws - 20 pack	ST099320
#14 x 1-1/2in Self-tapping Screws - 20 pack	ST099520
M8 x 80mm Stainless Steel Hex Head (13mm) Screw - 1 ct.	SS009880
Vertical Cable Replacement Kit for Stair or Deck	VC681000K

B=Black, W=White, Z=Bronze (where applicable)

VERTICAL CABLE REPLACEMENT PARTS	
36in Vertical Cable Repair Kit	VC081000
Vertical Cable Tension Block & Set Screws	CR028101
Allen Wrench, M2.5 Short Arm, Vertical Cable	CRO07006
36in Vertical Cable Stiffener	RPO64136
42in Vertical Cable Stiffener	RPO64142
HORIZONTAL CABLE REPLACEMENT PARTS	
Cable Deck Support Picket	NPO63500
Cable Stair Support Picket	NP063501
Cable Deck Picket Plug	CR004301
Cable Stair Picket Plug	CR054301
Cable Stair Angle Washer	CRO04007
Cable Deck Post Hole Plug	CR004008
Cable Stair Post Hole Plug	CR004009
3in x 36in Cable 90° Corner Post Insert	BFO45536
0.25in Hole x 0.75in L Christmas Tree Clip - 0.728in Head	CL120262
1/8in T-316 Threaded Stud Receiver, 1/4in UNC thread (Body Length: 3-1/32in)	CRO04001
1/8in T-316 Cable Receiver (Body Length: 3-1/32in)	CRO04002
T-316 Bright Polished Fast Fitting Dome Cap	CR025001
Allen Wrench, M6, Horizontal Cable	CRO07007

B=Black, W=White, Z=Bronze (where applicable)

**FOR COMPLETE INSTALLATION INSTRUCTIONS, VISIT HARMONYRAILING.COM.**

# ADA HANDRAILS



## ADA PIPE RAIL AND 90° RETURN KIT

Kit includes:  
 1 - 94in Pipe  
 2 - 90° Wall Returns and Covers  
 2 - 3in Post Backer Plates  
 2 - Joiner Rings  
 6 - #10 x 1.5in Self-tapping Screws  
 4 - #8 x 3/4in Color Matched Self-tapping Screws  
 Installation Instructions

P/N: AD901102  
 B=Black, W=White, Z=Bronze



## ADA PIPE RAIL EXTENSION KIT

Kit includes:  
 1 - 94in Pipe  
 2 - 6in Joiners  
 2 - Joiner Rings  
 2 - Rail Support Brackets with adapters and caps  
 2 - 3in Post Backer Plates  
 6 - #10 x 1-1/2in Self-tapping Screws  
 8 - #8 x 3/4in Color Matched Self-tapping Screws  
 Installation Instructions

P/N: AD901103  
 B=Black, W=White, Z=Bronze



## ADA 90° RETURN KIT

Required when Pipe Rail is cut into two pieces. Does not include 94in pipe rail.

Kit includes:  
 2 - 90° Wall Returns and Covers  
 2 - 3in Post Backer Plates  
 2 - Joiner Rings  
 6 - #10 x 1-1/2in Self-tapping Screws  
 4 - #8 x 3/4in Color Matched Self-tapping Screws  
 Installation Instructions

P/N: AD901101  
 B=Black, W=White, Z=Bronze



## ADA HANDICAP LOOP KIT

Kit includes:  
 2 - Handicap Loops  
 2 - Rail Support Brackets with adapters and caps  
 2 - Adjustable Elbows  
 2 - 3in Post Backer Plates  
 12 - #8 x 3/4in Self-tapping Screws  
 6 - #10 x 1-1/2in Self-tapping Screws  
 Installation Instructions

P/N: AD901104  
 B=Black, W=White, Z=Bronze

ADA HANDRAILS CAN BE USED FOR STAIRS, RAMPS AND HORIZONTAL APPLICATIONS.

FIND INSTRUCTIONS AND INSTALL VIDEOS AT [HARMONYRAILING.COM](http://HARMONYRAILING.COM).



**ADA 1.5in x 94in Pipe Rail**  
 P/N AD903194

**90° Wall Return**  
 P/N AD905118

**ADA Support Bracket**  
 Use on 2in and 3in Posts.  
 P/N AD908102

**Inside Corner Mount**  
 P/N AD908599

**ADA 6in Pipe Joiner**  
 P/N AD905178

**ADA Handicap Loop**  
 P/N AD905168



**Straight End Wall Mount**  
 P/N AD905128

**ADA 90° Elbow**  
 P/N AD905158

**ADA Adjustable Elbow**  
 P/N AD958204  
 Order 4X #8x3/4in screws for each elbow (sold separately).

**ADA 1.5in Joiner Ring**  
 P/N AD905188

**ADA End Cap**  
 Available in black only.  
 P/N AD905198

**3in Post Backer Plate**  
 P/N AD905248



**Rail to Bracket Attach Screws**

#8 x 3/4in Self-tapping Screw. 20-pack. P/N ST091820  
 B=Black, W=White, Z=Bronze



**Bracket to Metal Post Attach Screws**

#10 x 1-1/2in Self-tapping Screw. 20-pack. P/N ST091020



**Support Bracket Attach Screws**

#14 x 1-1/2in Self-tapping Screw. 20-pack. P/N ST099520



# SCREEN RAIL SYSTEM



## 6FT W SCREEN RAIL PANEL KITS

- 1 - 6ft W Screen Rail Panel (Actual Length = 69.43in)
- 1 - 6ft Top Rail Snap
- 1 - 6ft Perimeter Channel
- 2 - Locating Blocks
- 6 - L Brackets
- 4 - #8 x 1in Self-tapping Screws
- 1 - 30ft x .315in Flat Screen Spline
- Installation Instructions
- 36in H Panel Kit - P/N: SK068306
- 42in H Panel Kit - P/N: SK068406
- B=Black, W=White, Z=Bronze



## SCREEN RAIL POST KITS

- 1 - Screen Post
- 4 - L Brackets
- 8 - #8 x 1in Self-tapping Screws
- Installation Instructions
- Used in conjunction with railing panel kit if opening is over 6ft
- 8.5ft Kit - P/N: SK042208
- 12ft Kit - P/N: SK042212
- B=Black, W=White, Z=Bronze




## SCREEN RAIL PERIMETER CHANNEL KITS

- 2 - Perimeter Channels
- 8 - L Brackets
- 1 - 30ft x .315in Flat Screen Spline
- Installation Instructions
- 8.5ft Kit - P/N: SK002208
- 12ft Kit - P/N: SK002212
- B=Black, W=White, Z=Bronze
- NOTE:** Perimeter Channels may be used separately, without railings. However, most building codes require railings if screen enclosure is over 30in from ground level.




## SCREEN RAIL DOOR FRAME KITS

- 2 - Screen Posts
- 1 - Two-Piece 3ft Screen Post
- 1 - 3ft Perimeter Channel
- 4 - Locating Blocks
- 3 - L Brackets
- 8 - #8 x 1in Self-tapping Screws
- 1 - 30ft x .315in Flat Screen Spline
- Installation Instructions
- 8.5ft Kit - P/N: SK024208
- 12ft Kit - P/N: SK024212
- B=Black, W=White, Z=Bronze



# ALUMINUM FRAMING SYSTEM

The Harmony Railing® Aluminum Framing System is available in a variety of sizes and configurations. Contact your representative for more information.




# 1/2in x 3/4in FENCE SYSTEM


Fence panel size options may vary. Contact your Sales Representative for current offering.

Uses patented Ultralox Interlocking® assembly


## 1/2in x 3/4in BALUSTER FENCE PANELS



48in H x 6ft W - P/N: HF621406  
48in H x 8ft W - P/N: HF621408



54in H x 6ft W - P/N: HF631506  
54in H x 8ft W - P/N: HF631508



60in H x 6ft W - P/N: HF631606  
60in H x 8ft W - P/N: HF631608

Fence Panel Kits Include: Preassembled Fence Panel, Fence Cap (top rail cover), Panel Attach Kit for securing to two posts and Installation Instructions. Actual Panel Lengths: 6ft Panels = 69.43in, 8ft Panels = 91.31in. Actual Panel Heights: 48in Panels = 46.24in; 54in Panels = 52.12in; 60in Panels = 58.12in.

## 1/2in x 3/4in BALUSTER FENCE GATES



48in H x 48in W - P/N: HG671448



54in H x 48in W - P/N: HG671454



60in H x 48in W - P/N: HG671460

Gate Kits Include: Pre-Assembled Gate Panel, Self-Closing Hinges, Keyed Latching Hardware, Installation Instructions. Actual Gate Lengths: 47in. Actual Gate Heights: 48in Gates = 49.9in; 54in Gates = 55.9in; 60in Gates = 61.9in.

## SURFACE MOUNT FENCE POSTS



48in H x 2in W - P/N: HP631248  
48in H x 3in W - P/N: HP631348



54in H x 2in W - P/N: HP631254  
54in H x 3in W - P/N: HP631354



60in H x 2in W - P/N: HP631260  
60in H x 3in W - P/N: HP631360

## BURIED FENCE POSTS



48in H x 2in W - P/N: HP631280  
48in H x 3in W - P/N: HP631380



54in H x 2in W - P/N: HP631286  
54in H x 3in W - P/N: HP631386



60in H x 2in W - P/N: HP631292  
60in H x 3in W - P/N: HP631392

Surface Mount Fence Posts include: Pre-Assembled Post and Base Plate, Base Plate Plugs and Post Cap. Actual Surface Mount Post Heights: 48in Posts = 49.375in; 54in Posts = 55.375in; 60in Posts = 61.375in.

Buried Fence Posts include Aluminum Fence Post and Post Cap. Actual Buried Post Heights: 48in Posts = 80in; 54in Posts = 86in; 60in Posts = 92in.



### FENCE ATTACH KIT

Required when fence panel is cut and attaching more than one section. P/N: HF671300



### 22.5° FENCE ATTACH KIT

Required for 45° fence corners. Refer to installation instructions for proper post placement. P/N: HF671322

### For all parts on this page add: B=Black, W=White, Z=Bronze

All fencing is offered in an architectural grade powder coat. Contact your Harmony railing sales representative for all available sizes.

# 3/4in x 3/4in FENCE SYSTEM

Fence panel size options may vary. Contact your Sales Representative for current offering.

Uses patented Ultralox Interlocking® assembly


## 3/4in x 3/4in BALUSTER FENCE PANELS




48in H x 6ft W - P/N: HF631406  
48in H x 8ft W - P/N: HF631408



54in H x 6ft W - P/N: HF631456  
54in H x 8ft W - P/N: HF631468



60in H x 6ft W - P/N: HF631506  
60in H x 8ft W - P/N: HF631508



72in H x 6ft W - P/N: HF631606  
72in H x 8ft W - P/N: HF631608

Fence Panel Kits Include: Preassembled Fence Panel, Fence Cap (top rail cover), Panel Attach Kit for securing to two posts and Installation Instructions. Actual Panel Lengths: 6ft Panels = 69.43in, 8ft Panels = 91.31in. Actual Panel Heights: 48in Panels = 46.24in; 54in Panels = 52.12in; 60in Panels = 58.12in; 72in Panels = 70.12in.

## 3/4in x 3/4in BALUSTER FENCE GATES



48in H x 48in W - P/N: HF631448



54in H x 48in W - P/N: HF631454



60in H x 48in W - P/N: HF631460



72in H x 48in W - P/N: HF631472

Gate Kits Include: Pre-Assembled Gate Panel, Self-Closing Hinges, Keyed Latching Hardware, Installation Instructions. Actual Gate Lengths: 47in. Actual Gate Heights: 48in Gates = 49.9in; 54in Gates = 55.9in; 60in Gates = 61.9in; 72in Gates = 74.53in.

## SURFACE MOUNT FENCE POSTS



48in H x 2in W - P/N: HP631248  
48in H x 3in W - P/N: HP631348



54in H x 2in W - P/N: HP631254  
54in H x 3in W - P/N: HP631354



60in H x 2in W - P/N: HP631260  
60in H x 3in W - P/N: HP631360



72in H x 2in W - P/N: HP631272  
72in H x 3in W - P/N: HP631372

## BURIED FENCE POSTS



48in H x 2in W - P/N: HP631280  
48in H x 3in W - P/N: HP631380



54in H x 2in W - P/N: HP631286  
54in H x 3in W - P/N: HP631386



60in H x 2in W - P/N: HP631292  
60in H x 3in W - P/N: HP631392



72in H x 2in W - P/N: HP631204  
72in H x 3in W - P/N: HP631304

Surface Mount Fence Posts include: Pre-Assembled Post and Base Plate, Base Plate Plugs and Post Cap. Actual Surface Mount Post Heights: 48in Posts = 49.375in; 54in Posts = 55.375in; 60in Posts = 61.375in; 72in Posts = 74in.

Buried Fence Posts include Aluminum Fence Post and Post Cap. Actual Buried Post Heights: 48in Posts = 80in; 54in Posts = 86in; 60in Posts = 92in; 72in Posts = 104in.



### FENCE ATTACH KIT

Required when fence panel is cut and attaching more than one section. P/N: HF671300



### 22.5° FENCE ATTACH KIT

Required for 45° fence corners. Refer to installation instructions for proper post placement. P/N: HF671322

**For all parts on this page add:**  
**B=Black, W=White, Z=Bronze**

All fencing is offered in an architectural grade powder coat. Contact your Harmony railing sales representative for all available sizes.

# HARMONY RAILING® BALUSTER RAILING PLANNER

(36IN HIGH SYSTEM SHOWN)



**POST-TO-SURFACE MOUNTING SCREWS:**

RESIDENTIAL DECKS – 5/16" X 6" EXTERIOR TORX/STAR DRIVE CONSTRUCTION SCREWS  
 COMMERCIAL DECKS – 3/8" X 6" EXTERIOR TORX/STAR DRIVE CONSTRUCTION SCREWS  
 RESIDENTIAL CONCRETE – TAPCON® 5/16" X 3" HEX WASHER HEAD CONCRETE ANCHOR

WHAT YOU WILL NEED	VICT. P/N	ALTA P/N	QTY
<b>PREASSEMBLED ALUMINUM BALUSTER PANELS</b>			
6ft x 36in Baluster Panel (actual length 69.43in)	HR362306	HR862306	
6ft x 42in Baluster Panel (actual length 69.43in)	HR362406	HR862406	
8ft x 36in Baluster Panel (actual length 91.31in)	HR362308	HR862308	
8ft x 42in Baluster Panel (actual length 91.31in)	HR362408	HR862408	
6ft x 36in Continuous Rail (act. lgth 69.43in)*		HR062306	
6ft x 42in Continuous Rail (act. lgth 69.43in)*		HR062406	
8ft x 36in Continuous Rail (act. lgth 91.31in)*		HR062308	
8ft x 42in Continuous Rail (act. lgth 91.31in)*		HR062408	
<b>PREASSEMBLED ALUMINUM BALUSTER STAIR PANELS</b>			
6ft x 36in Stair Panel (actual length 69.43in)	HS352306	HS852306	
8ft x 36in Stair Panel (actual length 91.31in)	HS352308	HS852308	
6ft x 36in Continuous Stair Panel (69.43in)*		HS052306	
6ft x 42in Continuous Stair Panel (69.43in)*		HS052406	
8ft x 36in Continuous Stair Panel (91.31in)*		HS052308	
8ft x 42in Continuous Stair Panel (91.31in)*		HS052408	

\*Top rails sold separately with Continuous Rail and Continuous Stair Panels.

**Part Number Plus Color Identifier:** B=Black, W=White, Z=Bronze

WHAT YOU WILL NEED	VICT. P/N	ALTA P/N	QTY
<b>ALUMINUM POST KITS</b>			
INCLUDES: POST AND BASE PLATE, POST CAP, AND POST BASE VINYL SKIRT.			
36in x 3in Post Kit (actual length 38.25in)		HK441336	
42in x 3in Post Kit (actual length 43.5in)		HK441342	
48in x 3in Post Kit (actual length 48in)		HK441348	
36in x 2in Post Kit (actual length 34.06in)		HK341236	
42in x 2in Post Kit (actual length 39.625in)		HK341242	
48in x 2in Post Kit (actual length 48in)		HK341248	
<b>ADDITIONAL KITS</b>			
Continuous Top Rail - 18ft (B,W,Z)	VT393118	AL893118	
Deck & Stair Panel Attach Kit		HC39500	
22.5° Panel Attach Kit		HC06422	
45° Wall Mount Kit		HC06445	
Straight Wall Mount Kit	HC39100	HC89100	
Rail Clip Jig/Touch-Up Paint		HJ39700	
36in Gate Kit (adjustable up to 48in wide for 49in openings)		CG601349	
42in Gate Kit (adjustable up to 48in wide for 49in openings)		CG601449	

Prior to construction, check with your local regulatory agency for special code requirements in your area. Common railing height is 36in or 42in. Never span posts more than 8ft on center for baluster railing systems and 6ft on center for glass railing systems. Always ensure there is proper blocking under each post as per installation instructions. Read installation instructions and view installation videos to get a complete understanding of how the Harmony Railing® products assemble. Written installation instructions and videos can be found online at [HarmonyRailing.com](http://HarmonyRailing.com).

**HELPFUL ORDERING INFORMATION:**

- Baluster section kits include attachment clips and screws. If panels are cut and two pieces are used for installation, a separate attachment kit must be purchased.
- Anchors and fasteners to secure posts to concrete or wood are **NOT INCLUDED** in kits.
- Maximum post spacing on deck for baluster railing is 8ft on center and glass railing is 6ft on center.
- If using 1/4in tempered glass panel kit, glass panels must be purchased separately from a local glass company.

**IMPORTANT NOTES:**

- Actual baluster panel sizes: 6ft Panels = 69.43in; 8ft Panels = 91.31in.
- 3in posts are required to reach 6ft & 8ft lengths.
- Stair railing panels are shipped at a 37° angle. Panels are adjustable and will accommodate 30-40° stair angles.  
**CAUTION:** Over adjusting stair panels will cause loose and rattling balusters.
- 45° deck angles require 22.5° clips applied to each side of the post. The 22.5° clip kit is sold **SEPARATELY**.
- Using 2 Posts at top of stairs is recommended if compound angle cut is required.



# 1/4IN TEMPERED GLASS RAILING PLANNER

(36IN HIGH SYSTEM SHOWN)



WHAT YOU WILL NEED	VICT. P/N	ALTA P/N	QTY
<b>GLASS FRAME SECTIONS</b>			
6ft Aluminum Frame for Full 1/4in Tempered Glass Panel (Actual length 69.43in, Top Rail not included)	HG031206		
Top Rail Snap - 69.43in	VT393106	AL893106	
1/4in Tempered Glass Panels (Must be ordered from a local glass company)	N/A	N/A	
<b>PREASSEMBLED ALUMINUM BALUSTER STAIR PANELS</b>			
6ft x 36in Stair Panel (actual length 69.43in)	HS352306	HS852306	
8ft x 36in Stair Panel (actual length 91.31in)	HS352308	HS852308	
6ft x 36in Continuous Stair Panel (69.43in)*	HS052306		
6ft x 42in Continuous Stair Panel (69.43in)*	HS052406		
8ft x 36in Continuous Stair Panel (91.31in)*	HS052308		
8ft x 42in Continuous Stair Panel (91.31in)*	HS052408		

\*Top rails sold separately with Glass Frame Sections, Continuous Rail and Continuous Stair Panels.

**Part Number Plus Color Identifier:** B=Black, W=White, Z=Bronze

WHAT YOU WILL NEED	VICT. P/N	ALTA P/N	QTY
<b>ALUMINUM POST KITS</b>			
INCLUDES: POST AND BASE PLATE, POST CAP, AND POST BASE VINYL SKIRT.			
36in x 3in Post Kit (actual length 38.25in)		HK441336	
42in x 3in Post Kit (actual length 43.5in)		HK441342	
48in x 3in Post Kit (actual length 48in)		HK441348	
36in x 2in Post Kit (actual length 34.06in)		HK341236	
42in x 2in Post Kit (actual length 39.625in)		HK341242	
48in x 2in Post Kit (actual length 48in)		HK341248	
<b>ADDITIONAL KITS</b>			
Continuous Top Rail - 18ft (B,W,Z)	VT393118	AL893118	
Wood Grain Continuous Top Rail - 18ft (G,O)	VT393118	N/A	
Wood Grain Top Rail - 8ft (G,O)	VT393108	N/A	
Glass Panel Attach Kit		HCO3400	
22.5° Glass Panel Attach Kit		HCO3422	
45° Wall Mount Kit		HCO6445	
Straight Wall Mount Kit	HC39100	HC89100	
Rail Clip Jig/Touch-Up Paint		HJ39700	
36in Gate Kit (adjustable up to 48in wide for 49in openings)		CG681349	
42in Gate Kit (adjustable up to 48in wide for 49in openings)		CG681449	

Prior to construction, check with your local regulatory agency for special code requirements in your area. Common railing height is 36in or 42in. Never span posts more than 8ft on center for baluster railing systems and 6ft on center for glass railing systems. Always ensure there is proper blocking under each post as per installation instructions. Read installation instructions and view installation videos to get a complete understanding of how the Harmony Railing® products assemble.

Written installation instructions and videos can be found online at [HarmonyRailing.com](http://HarmonyRailing.com).

## HELPFUL ORDERING INFORMATION:


- Baluster section kits include attachment clips and screws. If panels are cut and two pieces are used for installation, a separate attachment kit must be purchased.
- Anchors and fasteners to secure posts to concrete or wood are **NOT INCLUDED** in kits.
- Maximum post spacing on deck for baluster railing is 8ft on center and glass railing is 6ft on center.
- If using 1/4in tempered glass panel kit, glass panels must be purchased separately from a local glass company.

## IMPORTANT NOTES:

- Actual baluster panel sizes: 6ft Panels = 69.43in; 8ft Panels = 91.31in.
- 3in posts are required to reach 6ft & 8ft lengths.
- Stair railing panels are shipped at a 37° angle. Panels are adjustable and will accommodate 30-40° stair angles.  
**CAUTION:** Over adjusting stair panels will cause loose and rattling balusters.
- 45° deck angles require 22.5° clips applied to each side of the post. The 22.5° clip kit is sold **SEPARATELY**.
- Using 2 Posts at top of stairs is recommended if compound angle cut is required.

# VERTICAL CABLE RAILING PLANNER

(36IN HIGH SYSTEM SHOWN)



**POST-TO-SURFACE MOUNTING SCREWS:**

- RESIDENTIAL DECKS – 5/16" X 6" EXTERIOR TORX/STAR DRIVE CONSTRUCTION SCREWS
- COMMERCIAL DECKS – 3/8" X 6" EXTERIOR TORX/STAR DRIVE CONSTRUCTION SCREWS
- RESIDENTIAL CONCRETE – TAPCON® 5/16" X 3" HEX WASHER HEAD CONCRETE ANCHOR

WHAT YOU WILL NEED	VICT. P/N	ALTA P/N	QTY
<b>VERTICAL CABLE RAILING PANELS</b>			
36in H x 6ft W Vertical Cable Panel (act. length 69.43in)	VC662306	VC162306	
36in H x 6ft W Vertical Cable Stair Panel (act. length 69.43in)	VC652306	VC152306	
36in H x 8ft W Vertical Cable Panel (act. length 91.31in)	VC662308	VC162308	
42in H x 6ft W Vertical Cable Panel (act. length 69.43in)	VC662406	VC162406	
42in H x 6ft W Vertical Cable Stair Panel (act. length 69.43in)	VC652406	VC152406	
42in H x 8ft W Vertical Cable Panel (act. length 91.31in)	VC662408	VC162408	
<b>ALUMINUM POST KITS</b> INCLUDES: POST AND BASE PLATE, POST CAP, AND POST BASE VINYL SKIRT.			
36in H x 3in W Post Kit (actual length 38.25in)	HK441336		
42in H x 3in W Post Kit (actual length 43.5in)	HK441342		
48in H x 3in W Post Kit (actual length 48in)	HK441348		
36in H x 2in W Post Kit (actual length 34.06in)	HK341236		
42in H x 2in W Post Kit (actual length 39.625in)	HK341242		
48in H x 2in W Post Kit (actual length 48in)	HK341248		

WHAT YOU WILL NEED	VICT. P/N	ALTA P/N	QTY
<b>ADDITIONAL KITS</b>			
Top Rail Snap - 6ft	VT393106	AL893106	
Deck & Stair Panel Attach Kit		HC39500	
22.5° Panel Attach Kit		HC06422	
45° Wall Mount Kit		HC06445	
Straight Wall Mount Kit	HC39100	HC89100	
Rail Clip Jig/Touch-Up Paint		HJ39700	
36in H Gate Kit (adjustable up to 49in wide for 50in openings)		HG07518	
42in H Gate Kit (adjustable up to 49in wide for 50in openings)		HG07520	

**Part Number Plus Color Identifier:** B=Black, W=White, Z=Bronze

Prior to construction, check with your local regulatory agency for special code requirements in your area. Common railing height is 36in or 42in. Never span posts more than 8ft on center for baluster railing systems and 6ft on center for glass railing systems. Always ensure there is proper blocking under each post as per installation instructions. Read installation instructions and view installation videos to get a complete understanding of how the Harmony Railing® products assemble.

**HELPFUL ORDERING INFORMATION:**


1. Baluster section kits include attachment clips and screws. If panels are cut and two pieces are used for installation, a separate attachment kit must be purchased.
3. Anchors and fasteners to secure posts to concrete or wood are **NOT INCLUDED** in kits.
4. Maximum post spacing on deck for vertical cable railing is 6ft on center.

Written installation instructions and videos can be found online at [HarmonyRailing.com](http://HarmonyRailing.com).

**IMPORTANT NOTES:**

- Actual panel lengths: 6ft Panels = 69.43in; 8ft Panels = 91.31in.
- 3in posts are required to reach 6ft lengths.
- Stair railing panels will accommodate 30-40° stair angles.
- 45° deck angles require 22.5° clips applied to each side of the post. The 22.5° clip kit is sold **SEPARATELY**.
- Using 2 Posts at top of stairs is recommended if compound angle cut is required.

# HORIZONTAL CABLE RAILING PLANNER



WHAT YOU WILL NEED	VICT. P/N	ALTA P/N	QTY
<b>HORIZONTAL CABLE RAILING FRAME KITS</b>			
36in / 42in H x 6ft W Horizontal Cable Deck Full Frame Kit	TF661306	TF161306	
36in / 42in H x 6ft W Horizontal Cable Deck Top Rail Kit	TR661306	TR161306	
36in / 42in H x 8ft W Horizontal Cable Deck Full Frame Kit	TF661308	TF161308	
36in / 42in H x 8ft W Horizontal Cable Deck Top Rail Kit	TR661308	TR161308	
36in / 42in H x 6ft W Horizontal Cable Stair Full Frame Kit	TF651306	TF151306	
36in / 42in H x 6ft W Horizontal Cable Stair Top Rail Kit	TR651306	TR151306	
36in / 42in H x 8ft W Horizontal Cable Stair Full Frame Kit	TF651308	TF151308	
36in / 42in H x 8ft W Horizontal Cable Stair Top Rail Kit	TR651308	TR151308	
<b>HORIZONTAL CABLE KITS</b>			
5ft Horizontal Cable Kit for 3in posts	CW60305		
10ft Horizontal Cable Kit for 3in posts	CW60310		
15ft Horizontal Cable Kit for 3in posts	CW60315		
20ft Horizontal Cable Kit for 3in posts	CW60320		
25ft Horizontal Cable Kit for 3in posts	CW60325		
30ft Horizontal Cable Kit for 3in posts	CW60330		
35ft Horizontal Cable Kit for 3in posts	CW60335		
40ft Horizontal Cable Kit for 3in posts	CW60340		
45ft Horizontal Cable Kit for 3in posts	CW60345		
50ft Horizontal Cable Kit for 3in posts	CW60350		
55ft Horizontal Cable Kit for 3in posts	CW60355		
60ft Horizontal Cable Kit for 3in posts	CW60360		
5ft Horizontal Cable Kit for 2in posts	CW90205		
10ft Horizontal Cable Kit for 2in posts	CW90210		
15ft Horizontal Cable Kit for 2in posts	CW90215		
20ft Horizontal Cable Kit for 2in posts	CW90220		
25ft Horizontal Cable Kit for 2in posts	CW90225		
30ft Horizontal Cable Kit for 2in posts	CW90230		
35ft Horizontal Cable Kit for 2in posts	CW90235		
40ft Horizontal Cable Kit for 2in posts	CW90240		
45ft Horizontal Cable Kit for 2in posts	CW90245		
50ft Horizontal Cable Kit for 2in posts	CW90250		
55ft Horizontal Cable Kit for 2in posts	CW90255		
60ft Horizontal Cable Kit for 2in posts	CW90260		

Prior to construction, check with your local regulatory agency for special code requirements in your area. Common railing height is 36in or 42in. Never span posts more than 8ft on center for horizontal cable railing systems. Always ensure there is proper blocking under each post as per installation instructions. Read installation instructions and view installation videos to get a complete understanding of how the Harmony Railing® products assemble.

#### HELPFUL ORDERING INFORMATION:

- Frame kits include attachment tools and screws. If panels are cut and two pieces are used for installation, a separate attachment kit must be purchased.
- Anchor and fasteners to secure posts to concrete or wood are **NOT INCLUDED** in kits.
- Maximum post spacing on deck and stairs for horizontal cable railing is 8ft on center.

WHAT YOU WILL NEED	VICT. P/N	ALTA P/N	QTY
<b>HORIZONTAL CABLE ALUMINUM POST KITS</b>			
INCLUDES: POST AND BASE PLATE, POST CAP, AND POST BASE VINYL SKIRT.			
36in H x 3in W Horizontal Cable End Post Kit		PC6E1336	
36in H x 3in W Horizontal Cable Inline Post Kit		PC6I1336	
36in H x 3in W Horizontal Cable Corner Post Kit		PC6C1336	
42in H x 3in W Horizontal Cable Inline Stair Post Kit		PC6S1342	
42in H x 3in W Horizontal Cable Stair Bottom Post Kit		PC6B1342	
42in H x 3in W Horizontal Cable End Post Kit		PC6E1342	
42in H x 3in W Horizontal Cable Inline Post Kit		PC6I1342	
42in H x 3in W Horizontal Cable Corner Post Kit		PC6C1342	
48in H x 3in W Horizontal Cable Inline Stair Post Kit		PC6S1348	
48in H x 3in W Horizontal Cable Stair Bottom Post Kit		PC6B1348	
36in H x 2in W Horizontal Cable End Post Kit		PC6E1236	
36in H x 2in W Horizontal Cable Inline Post Kit		PC6I1236	
36in H x 2in W Horizontal Cable Corner Post Kit		PC6C1236	
42in H x 2in W Horizontal Cable Inline Stair Post Kit		PC6S1242	
42in H x 2in W Horizontal Cable End Post Kit		PC6E1242	
42in H x 2in W Horizontal Cable Inline Post Kit		PC6I1242	
42in H x 2in W Horizontal Cable Corner Post Kit		PC6C1242	
48in H x 2in W Horizontal Cable Inline Stair Post Kit		PC6S1248	
<b>TOOLS</b>			
Cable Gripper Tool		TC097606	
Horizontal Cable Tool Kit. Includes: cable threading tool, 90° cable threading tool and cable release tool.		TK32750	
Stainless Steel Cable Cutter		TC697703	
<b>ADDITIONAL KITS</b>			
Top Rail Snap - 6ft	VT393106	AL893106	
Deck & Stair Panel Attach Kit		HC39500	
22.5° Panel Attach Kit		HC06422	
Rail Clip Jig/Touch-Up Paint		HJ39700	
36in H Gate Kit (adjustable up to 49in wide for 50in openings)		HG07518	
42in H Gate Kit (Width is not adjustable. Actual width: 49in wide for 50in openings)		HG07520	

Part Number Plus Color Identifier: B=Black, W=White, Z=Bronze

#### IMPORTANT NOTES:

- Actual panel lengths: 6ft Panels = 69.43in; 8ft Panels = 91.31in.
- 3in posts are required to reach 6ft & 8ft lengths.
- 45° deck angles require 22.5° clips applied to each side of the post. The 22.5° clip kit is sold **SEPARATELY**.
- Using 2 Posts at top of stairs is recommended if compound angle cut is required.

# TOOLS RECOMMENDED FOR INSTALLATION



Cordless Drill  
(hammer drill for concrete)



Level



Tape Measure and  
Pencil



Safety Glasses



Bar Clamps



Miter Saw  
(with nonferrous blade)



84-Tooth Nonferrous  
Blade




3/16in Drill Bit



3/16in Masonry Drill Bit  
(concrete applications)



5/16in & 5/8in Drill Bits  
(for LED Lighting application)



6in #2 Square Drive Bit



Horizontal Cable  
Tool Kit



Cable Gripper Tool



Stainless Steel Cable  
Cutter

# SYSTEM EVALUATION

Harmony Railing® (Harmony) aluminum baluster systems have been evaluated for structural integrity by an independent laboratory as per ICC-ES AC273 - acceptance criteria (approved/ revised October 2020) for handrails and guards. The Harmony aluminum railing systems have been evaluated with 1/2in x 3/4in aluminum balusters (6063-T5) assembled using the patented Ultralox Interlocking® assembly process by which guardrail infill components are press-locked together. Harmony's 1/4in tempered glass panel system (ANSI Z97.1 tempered glass) has been evaluated with a total railing span of 72in with a Harmony 3in post attached at each end and secured to a concrete substrate with 4-Hilti KH-EZ 1/4in x 3in concrete anchors. When the guardrail is installed in configurations other than described in the installation instructions, the installation configuration and fastening detail must be specified by a licensed engineer.

When Harmony aluminum railing systems are assembled under the conditions described above, the railings meet the guardrail requirements of 1607.7.1.1 of the 2018 International Building Code (IBC).

When the Harmony guardrail is installed in configurations other than described above, each installation shall be designed using numerical calculation methods by a registered professional engineer licensed in the state in which the project is constructed. Sealed shop drawings shall be made available to interceded parties to demonstrate compliance with application in which the project is constructed.

If Harmony railings are installed contrary to the specific assembly described above and sealed engineering drawings are not available, then the railing is intended for decorative purposes only and cannot be used in applications where structural railing systems are required by local or international building code.

The diagrams and instructions provided with each system are for illustration purposes only and are not meant to replace a licensed professional. Any construction or use of the product must be in accordance with all local zoning and/or building codes. The consumer assumes all risks and liability associated with the construction or use of this product. The consumer or contractor should take all necessary steps to ensure the safety of everyone involved in the project, including, but not limited to, wearing the appropriate safety equipment. Except as contained in the written limited warranty, Harmony does not provide any other warranty; either expressed or implied, and shall not be liable for any damages, including consequential damages.

© 2022, 2023 Harmony Railing® is a WES LLC Company  
HarmonyRailing.com



**Full Glass Panels with ADA Handrails**



**Drink Rail System on White Baluster Railing**

# HARMONY RAILING®

## 20-YEAR LIMITED WARRANTY

Harmony Railing® warrants its railing products to be free from manufacturing defects in material and workmanship to the original consumer purchaser. In addition to manufacturing defects, this warranty covers cracking, peeling and blistering of the finish of our products.

This warranty does not cover damage caused by abnormal or improper use, improper product installation, accidents, alterations, welding, neglect, damage by lawn care equipment, abrasion, harsh chemicals, pool chemicals, snow and ice removal chemicals, air pollutants, improper service or lack of and damage caused by fire, flood or acts of God. This warranty does not cover corrosion from cuts, scratches, dents or nicks. Products with a residential installation located one (1) mile or less from any coastline shall have a three (3) year warranty from the date of purchase. Products located 1 mile or less from any coastline shall qualify for a 10-year Limited Warranty if an AkzoNobel Interpon 700 polyester epoxy primer (EL015Q) is applied prior to the application of the above Interpon D2000 Super Polyester Architectural Powder Coating (Ultralox Coastal Coating). AkzoNobel Interpon 700 polyester epoxy primer (EL015Q) powder coating shall only be applied by approved Interpon D applicators as per above instructions. Products in direct contact with saltwater do not qualify for any Ultralox Interlocking warranty.

### REGISTER YOUR PRODUCT

We want to be sure you have the safety and security of knowing that your Harmony product is here to stay. To activate the warranty on your product, please complete the registration form online within sixty (60) days of your purchase date. Please visit: [HarmonyRailing.com](http://HarmonyRailing.com).

### CLAIM PROCEDURE

To make a claim under this Warranty to receive replacement product, the original consumer must, within 90 days of actual or constructive notice of any covered defect in the product, do the following:

- (1) Prepare a letter that includes the following:
  - a. A list of the number of pieces and the size of each piece for which the claim is made.
  - b. Proof of Purchase of the products, as shown on the original invoice.
  - c. Proof of Warranty - Original purchaser or homeowner must have registered their product online at [HarmonyRailing.com](http://HarmonyRailing.com) within 60 days of purchase date.
- (2) Mail the above to:  
Harmony Railing  
2737 West Service Road  
Eagan, MN 55121
- (3) Email to: [warranty@harmonyrailing.com](mailto:warranty@harmonyrailing.com)



### CONDITIONS AND EXCLUSIONS OF THIS WARRANTY:

#### CLEANING AND CARE INSTRUCTION MUST BE FOLLOWED TO HONOR WARRANTY.

THIS WARRANTY IS NOT TRANSFERABLE. THE AMOUNT OF YOUR RESTITUTION, IF ELIGIBLE, WILL NOT INCLUDE LABOR TO REMOVE THE EXISTING PRODUCT OR INSTALL ANY REPLACEMENT COMPONENTS, SHIPPING CHARGES, SALES TAX OR ANY OTHER CHARGES, NOR WILL HARMONY RAILING® PROVIDE SUCH LABOR OR SERVICE.

THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER EXPRESS WARRANTIES. HARMONY RAILING® MAKES NO OTHER EXPRESS WARRANTIES AND DOES NOT AUTHORIZE ANY OTHER PERSON OR AGENT TO MAKE ANY OTHER EXPRESS WARRANTIES. HARMONY RAILING® NEITHER ASSUMES NOR AUTHORIZES ANY OTHER LIABILITY OR OBLIGATION IN WARRANTY, INCLUDING WITHOUT LIMITATION, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THEIR PRODUCTS. IN NO EVENT SHALL HARMONY RAILING® BE LIABLE FOR ANY CONSEQUENTIAL, SPECIAL OR INCIDENTAL DAMAGES ARISING OUT OF OR CONNECTED WITH THE PURCHASE OR USE OF THEIR PRODUCTS OR FOR ANY BREACH OF WARRANTY.

SOME STATES DO NOT ALLOW LIMITATIONS ON HOW LONG AN IMPLIED WARRANTY LASTS OR THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATIONS OR EXCLUSIONS MAY NOT APPLY TO YOU. THIS WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS, AND YOU MAY HAVE OTHER RIGHTS THAT VARY FROM STATE TO STATE. THIS WARRANTY IS APPLICABLE ONLY TO SYSTEMS INSTALLED WITHIN THE CONTINENTAL UNITED STATES AND CANADA.

# HARMONY RAILING®

## CLEANING AND MAINTENANCE GUIDE

---

### BACKGROUND

Harmony Railing® architectural powder coatings are organic coatings that must be regularly cleaned and maintained in order to ensure the decorative and protective properties of the coatings are retained. Records of all cleaning schedules and frequencies shall be kept and maintained by the customer according to the process outlined below and shall be available to Harmony Railing® upon request.

### CLEANING METHOD

**Usual maintenance of Products must adhere to the following steps:**

- Clean using an appropriate cleaning product, as defined below.
- Rinse with clear water.
- Wipe with a soft cloth.
- All surfaces shall be cleaned using a soft cloth or sponge, and no cloth shall be harsher than natural bristle brushes.

If the Product is subject to any hazardous and unusual environmental factors or is located within one (1) mile of the seashore, an estuary or marine environment, Harmony Railing® must be consulted on an individual project basis for best maintenance practices.

### CLEANING PRODUCTS

Before cleaning, the customer must consult and adhere to the underlying instructions contained within the Product Data Sheet available online at [HarmonyRailing.com](http://HarmonyRailing.com).

Usual maintenance cleaning may be done using water with a mild detergent (pH 5 to 8).

If atmospheric pollution has resulted in heavy soiling of the coating, some stains or marks may require stronger domestic products, such as alcohol, petroleum spirits, white spirits or bleach diluted to five percent (5%). In this instance, the customer must rinse the coating immediately after using the cleaning product.

In no circumstance shall any abrasive cleaner, polish or cleaners containing ketones or ether be used.

### FREQUENCY

**For all Products located within one (1) mile of the seashore:**

- Customer shall clean the Product six (6) times per year.
- The cleaning cycle shall commence within two (2) months of installation.
- Cleaning shall be conducted in intervals not to exceed two (2) months.
- Customer shall maintain fully documented records throughout the Warranty term.

**For all Products located more than one (1) mile of the seashore:**

- Customer shall clean the Product four (4) times per year.
- The cleaning cycle shall commence within three (3) months of installation.
- Cleaning shall be conducted in intervals not to exceed three (3) months.
- Customer shall maintain fully documented records throughout the Warranty term.

### ADDITIONAL FACTORS

Damage from installation, mechanical processes, jig marks and other related defects must be repaired immediately in order for the Warranty to remain in effect.

Protective tapes used in installation must be a in low-tacking quality and must not be left in contact with the surface for more than one (1) month.

Harmony Railing® must approve all sealants and mastics prior to installation in order for Warranty to remain in effect.

# REQUEST A FREE ESTIMATE



Visit [HarmonyRailing.com](https://www.harmonyrailing.com) for image galleries, technical data, resources or a **FREE ESTIMATE** for your project.

Our team is ready to help you get all of the information you need including a full parts list, an official technical take off drawing and top customer service. Scan the code to request yours now!



**HARMONY  
RAILING®**

[HarmonyRailing.com](https://www.harmonyrailing.com)

**(844) 724-5001**



©2024 Harmony Railing®, All Rights Reserved. Version 3.7  
Part # MH39650